

STÜWA Gravel-Pack Screens

ND	inch	inner ø	outer - ø	wall thickness of PVC-tube	outer - ø over gravel	thickness of gravel pack	approx. weight
mm		mm	mm	mm	about mm	mm	kg/m
35	1¼"	34.5	41.5	3.5	63	10.5	3.1
40	1½"	41	48	3.5	75	13.5	4.8
50	2"	52	60	4.0	92	16.0	6.1
80	3"	80	88	4.0	121	16.5	10.0
100	4"	103	113	5.0	143	15.0	11.5
115	4½"	115	125	5.0	157	16.0	13.5
125	5"	127	140	6.5	172	16.0	15.1
150	6"	150	165	7.5	196	15.5	16.5
175	7"	178	195	8.5	226	15.5	23.0
200	8"	205	225	10.0	261	18.0	30.0
250	10"	255	280	12.5	316	18.0	41.0
300	12"	301	330	14.5	366	16.0	48.5
350	14"	365	400	17.5	436	18.0	65.0
400	16"	411	450	19.5	482	16.0	74.0

material : PVC-U acc. to DIN 4925

slot sizes:	grain size	0.7 - 1.2	slot	0.75 mm
	grain size	1 - 2	slot	1.0 mm
	grain size	2 - 3	slot	1.5 mm
	grain size	3 - 5	slot	2.0 mm

coupling: nach DIN 4925

running length:	DN 35, 40, 50	1.0m
	DN 80 - DN 400 (1m-length is possible)	2.0m